

## DECLARATION

I, **Lubilo Foster**, hereby declare that the contents of this dissertation represent my own work and that it has not previously been submitted to this or any other university for any academic qualification.

.....

**Signed**

.....

**Date**

This work is subject to copyright.

All rights are reserved, whether the whole or part of the material is concerned, specifically those of translation, reprinting, re-use of illustrations, broadcasting, reproduction by photocopying machines or similar means, and storage in data banks.

©Lubilo Foster, Department of Geomatic Engineering, School of Engineering, The University of Zambia, 2016.

## CERTIFICATE OF APPROVAL

This thesis by **Lubilo Foster** is approved as partial fulfilment of the requirements for the award of the Master's Degree of Engineering (MEng) in Geoinformatics and Geodesy by the University of Zambia.

<b>Examiners:</b>	<b>Signature</b>	<b>Date</b>
1. ....	.....	.....
2. ....	.....	.....
3. ....	.....	.....
<b>Supervised by:</b>		
<b>Dr. P. Nsombo</b>	.....	.....

## Abstract

Geodetic Deformation Monitoring (GDM) plays a vital role in project safety and management. Geodetic measurements on dams are done to monitor change and rate of change in order to ensure safety. Kariba Dam suffers normal stresses, and strains mainly from temperature and hydrostatic pressure seasonal changes. These loads deflect the dam upstream/downstream in summer and winter, respectively. The deflections are currently monitored using a traditional deformation monitoring system by Zambezi River Authority (ZRA). However, more unexpected factors which were not catered for at design stage have rendered the traditional methods obsolete. These unexpected factors are: Reservoir Induced Seismicity (RIS), Plunge Pool scouring, Alkali Aggregate Reaction (AAR), landslide and earth-work vibrations. Thus, in this study, the dam was assessed to have new deformation patterns: Clockwise (southward) horizontal rotation of the north abutment, tangential movements of the dam northwards, increased upstream/upward swelling of the dam crest, and southward vertical rotation of the south and north bank. Due to the above deflections, the Kariba Dam arch has lost its original shape, with the arch ends buckling more than the spillway section. Human-related errors may worsen these deformations. The vertical and horizontal rotational tendencies resulted from anchor cables and landslide moments of forces on the south bank. AAR effect was analyzed as being of less concern because past findings proved it's subsiding. Poor geology destabilized the control points, thus rendering the classical monitoring system less accurate. To address the new deformations, a real-time, automated GNSS/LPS Online-based Control and Alarm System (GOCA) was designed for an early detection, alerting of landslide and its effects on the dam to classified users. This system applies GNSS and classical Local Positioning Sensors (LPS) such as Total Stations, and geotechnical instruments. It was recommended that prism array be installed urgently for use even under the classical methods for more deformation detection. This research has explained the puzzling new dam behaviour and substantiated the effects of the landslide which might have been worsened by earth work activities in the area with poor geology. Hence this research formed a basis for future studies and monitoring system improvements at the Kariba Dam through easy-to-understand analysis and visualizations of concepts and past deformation data presented mainly in form of tables by ZRA. The analysis included computations of rates of change of current deformations compared to the previous ones. The past and current deformation results were visualized in form of drawings and illustrations which helped link landslide forces to new dam deformations.

**Key words:** GDM, Kariba Dam, GNSS, RIS, AAR, GOCA, LPS, ZRA, Landslide, visualization techniques, prism array, south bank and traditional methods.

To my lovely daughter, Mirriam Mwaka Lubilo, who has brought joy into my life

## Acknowledgements

First and foremost, I would like to thank the Directorate of Research and Graduate Studies (DRGS) of the University of Zambia for having embarked on the Master's program at the University. Further, I would like to thank the DRGS for admitting me into this program.

To my sponsors, Southern African Science for Climate and Adaptive Land use (SASCAL), I say many thanks. My appreciation to SASCAL would be incomplete without thanking Dr. A. Mulolwa who facilitated my sponsorship.

In addition, I extend my appreciation to my supervisors, Dr. P. Nsombo and Mr. A. R. Mwanza for their valuable contributions to my research. I would like to also thank the department of Geomatic Engineering and the School of Engineering at large for facilitating my study.

Most importantly, I thank my Judges or Examiners for their positive contributions towards the success of my dissertation.

I also thank the Zambezi River Authority management and its technical team who provided an enabling environment for me to conduct a study on such a sensitive and vital infrastructure.

To UNZA bindery team, I extend my gratitude for their professional service of binding my thesis report.

I would not forget to thank Bishop Masiya and Marshal Chikoli for working tirelessly in providing me with a spiritual support and social advice during my tough times.

Leslie Szeftel and his wife, Lynn, deserve a special recognition for their ideas which, most of them, formed a basis for my analysis in this dissertation.

I finally thank my dear wife for her house chores, which without them; I would not have succeeded in my study.

## Table of Contents

Declaration.....	i
Certificate of Approval.....	ii
Abstract .....	iii
Dedication.....	iv
Acknowledgements.....	v
Table of Contents.....	vi
List of Figures.....	xi
List of Tables.....	xiii
Abbreviations.....	xiii
<b>1.0 Introduction</b>	
1.1 Problem Statement.....	3
1.2 Research Questions.....	4
1.3 Project Objective.....	4
1.3.1 Specific Objectives.....	4
1.4 Rationale.....	5
<b>2.0 Background</b>	
2.1 General.....	6
2.1.1 Kariba Dam design loads.....	6
2.1.1.1 Temperature Variations.....	8
2.1.1.2 Hydrostatic Pressure.....	8
2.1.1.3 Uplift pressure.....	9
2.1.1.4 Dam weight.....	9
2.1.2 Kariba Dam deformation monitoring.....	10
2.1.2.1 Geotechnical installations.....	10
2.1.2.2 Anchor Bars.....	11
2.1.2.3 Geodetic deformation monitoring system.....	11

2.1.2.4	Principal behind Kariba Dam monitoring.....	12
2.1.2.5	Kariba Dam reference networks.....	13
2.1.3	Unexpected dam stability threats.....	15
2.1.3.1	Plunge Pool erosion.....	15
2.1.3.2	South Bank Landslide.....	17
2.1.3.3	Alkali Aggregate Reaction (AAR).....	18
2.1.3.4	Unusual Dam behaviour.....	20
2.1.3.4.1	Tangential movement.....	20
2.1.3.4.2	Rotational movement.....	20
2.1.3.5	Reservoir Induced Seismicity (RIS).....	22
2.1.4	Landslide remedial measures.....	23
2.1.4.1	Slope maintenance.....	23
2.1.4.2	South bank network expansion.....	24
2.1.5	Kariba Dam stability concerns.....	25
2.1.5.1	Dam failure attributed to human errors.....	26
2.1.5.1.1	Vajont Dam failure.....	26
2.1.5.1.2	Teton Dam failure.....	27
<b>2.2.0</b>	<b>Theoretical Background.....</b>	<b>30</b>
2.2.1	Isaac Newton's laws of motion.....	30
2.2.1.1	First law.....	30
2.2.1.2	Second law.....	30
2.2.1.2.1	Velocity.....	30
2.2.1.2.2	Acceleration.....	31
2.2.1.3	Third law.....	31
2.2.2	Force acting at an angle.....	31
2.2.3	Moment or Torque of a force.....	32
2.2.4	Least Squares Network adjustment.....	33

2.2.4.1	Mathematical model.....	33
2.2.4.2	Surveyor's Reference System.....	35
2.2.4.2.1	Bearing and distance computations.....	35
2.2.4.2.2	Labelling and use of Map directions.....	35
<b>2.3.0</b>	<b>Modern Geodetic Deformation Monitoring.....</b>	<b>36</b>
2.3.1	GOCA System.....	37
2.3.1.1	Components of the GOCA System.....	37
2.3.2	GNSS Continuous Operating Reference Station (CORS).....	40
<b>3.0</b>	<b>Materials and Methods.....</b>	<b>42</b>
3.1	Flow Chart.....	43
3.2	Field work.....	44
3.2.1	Reconnaissance Survey.....	44
3.2.2	Instruments.....	44
3.3	Field Data Processing.....	46
3.4	Deformation Analysis and Results.....	47
3.4.1	Past reports used.....	47
3.4.2	Landslide and AAR effects on the dam.....	48
3.4.2.1	Investigative AAR-landslide effects analysis.....	49
3.4.3	Landslide deformation analysis on control pillars.....	49
3.4.3.1	Landslide effect on control pillars.....	51
3.4.4	Tree-dozer concept (force & its knock-off effect).....	55
3.4.5	Landslide Direction.....	56
3.4.6	System of Forces on the Kariba Dam.....	57
3.4.7	Velocity and Acceleration of the north arch-end movements.....	60
3.4.8	Force exerted on the north bank.....	61
3.4.9	Vertical Pillar displacements.....	61
3.4.10	Lateral control pillar displacements.....	63

3.4.11	Isolating AAR from landslide effects.....	66
3.4.11.1	AAR effects on the dam.....	66
3.4.11.2	Increased dam crest swelling.....	67
3.4.11.3	New dam behaviour.....	70
3.4.11.4	Other effects of the landslide on the dam.....	72
3.5	Current deformation monitoring system errors.....	72
3.5.1	Bearing and distance errors.....	73
3.5.2	Least squares adjustment failure.....	74
3.5.3	Inadequacy of the current monitoring method.....	75
3.5.3.1	Pendulum Flaws.....	76
3.5.3.1.1	South Bank vertical rotation.....	77
3.6	Rotational effects on the measurements.....	80
3.7	Other Rotation-related problems.....	80
3.8	Earth-work effects on dam stability.....	80
3.9	Reasons for misinterpretation.....	81
3.9.1	Inadequate landslide data capture.....	81
<b>4.0</b>	<b>Geodetic Deformation Monitoring System Design.....</b>	<b>83</b>
4.1	Reasons for the design.....	83
4.2	Conceptual Design.....	84
4.3	GNSS-RTS Physical design.....	85
4.3.1	Error handling using RTS-GNSS co-location.....	86
4.3.2	Design features.....	89
4.4	Prism Array design.....	91
4.5	Advantages of the upgraded system.....	93
4.6	Disadvantages.....	93
<b>5.0</b>	<b>Case Studies.....</b>	<b>95</b>
5.1	Automated deformation monitoring: Case study of Sermo Dam, Yogyakarta Province, Indonesia.....	95

5.1.1	Sensors installed.....	95
5.1.2	Leica GeoMoS software.....	96
5.2	GOCA deformation monitoring: Case study of Steenbras Dam, Cape Town, South Africa.....	96
5.2.1	Trimble 4D Control (T4D) Software.....	99
5.2.2	Advantages.....	100
5.3	Ultimate objective of the system upgrade.....	102
<b>6.0</b>	<b>Discussion.....</b>	<b>105</b>
<b>7.0</b>	<b>Conclusion and Recommendations.....</b>	<b>111</b>
7.1	Conclusion.....	111
7.2	Recommendations.....	113
<b>8</b>	<b>References.....</b>	<b>115</b>
<b>9</b>	<b>Appendices.....</b>	<b>120</b>
	Appendix A: Sermo dam GOCA system photos.....	120
	Appendix B: Control-Point Coordinates & Displacements.....	123
	Appendix C: Drawings derived from appendix B data.....	124

## List of Figures

- Figure 2.1: Kariba Dam location (left) and general view (right); courtesy of ZRA
- Figure 2.2: Cross section of Kariba Dam, viewed from Zimbabwean side (South Bank)
- Figure 2.3: Total Station (right) measuring to Prism (left); courtesy of ZRA
- Figure 2.4: Primary Geodetic Control Points; courtesy of ZRA
- Figure 2.5: Current status of the Plunge Pool; courtesy of ZRA
- Figure 2.6: Plunge Pool depths, longitudinal section of figure 2.5
- Figure 2.7: Cross-Sectional view of the Landslide zones of the South Bank
- Figure 2.8: Effects of AAR on the concrete arched dam; section view parallel to main dam Axis
- Figure 2.9: Northward movement of the dam
- Figure 2.10: Kariba Dam misalignment problem about its upstream-downstream Axis (Coyne and Bellier, 2011)
- Figure 2.11: Stone-pitched slope of the South Bank at Kariba Dam; Courtesy of ZRA
- Figure 2.12: Force resolutions into components
- Figure 2.13: Moment of a force
- Figure 2.14: Data-set of measured points of an object point (Larson and Farber, 2003)
- Figure 2.15: Schematic diagram of the GOCA system
- Figure 3.1: Flow chart of the research methodology
- Figure 3.2: separation process of AAR and landslide effects
- Figure 3.3: Kariba Dam Local Coordinate System orientation: Courtesy of ZRA
- Figure 3.4: Sketch of Table 3.2 control point deformations-cross section from SB2 to NB4
- Figure 3.5: Hint; Bull Dozer knocking down trees (left) and its knock-off effect (right)
- Figure 3.6: Control point network and the associated derived landslide force directions
- Figure 3.7: Illustrative Free-body Diagram of the Kariba Dam arch (not to scale)

Figure 3.8: 2012 Vertical displacements of monuments

Figure 3.9: 2015 Vertical displacements of monuments

Figure 3.10: Lateral-displacement bar chart of control points (see direction of drifts in drawing 1 in the appendices)

Figure 3.11: Photo showing dam crest sections with CD2 at 0 as center

Figure 3.12: Graphs showing AAR effect reduction; courtesy of ZRA

Figure 3.13: Graphs of annual rise rate of individual crest block; Courtesy of ZRA

Figure 3.14: Graphs of annual rise rate of individual crest blocks for south bank; courtesy of ZRA

Figure 3.15: AAR-Landslide effects on the dam

Figure 3.16: Total Station (left) mounted on unstable control point, SB17, (right); courtesy of ZRA

Figure 3.17: The scatter plots obtained at t1 (a) and time t2 (b)

Figure 3.18: Cross Sectional view; illustration of non-uniform dam deformation

Figure 3.19: Contradiction of pendulum readings

Figure 4.1: Schematic GOCA system design

Figure 4.2: Geodetic deformation monitoring system design for Kariba dam

Figure 4.3: Geodetic deformation monitoring system for Kariba Dam (Photos taken from Steenbras dam-SA)

Figure 4.4: Prism array for Kariba Dam monitoring

Figure 5.1: Co-located GNSS receiver with Prism; Courtesy of Trimble

Figure 5.2: S8 RTS (left) in its Cabin and target prism to the right; courtesy of Trimble

Figure 5.3: Protective cabin, housing the S8 total station as well as a GNSS receiver on top with the weather station (left) on the cabin roof; courtesy of Trimble

Figure 5.4: Shows the GNSS Base Station; courtesy of Trimble

Figure 5.5: Relationship between water level and south bank landslide

## List of Tables

Table 3.1: Digital Level accuracies

Table 3.2: Control Pillar Residuals (mm) of 2012; courtesy of ZRA

Table 3.3: Deformation Magnitudes and the derived Velocities & Accelerations

Table 3.4: Derived lateral displacement  $\mathbf{d}$  from the 2012 residuals in Table 3.2

Table 3.5: Doubtful negative pendulum readings

## Abbreviations/Acronyms

AAR.....	Alkali Aggregate Reaction
BoQs.....	Bill of Quantities
BOCs.....	Bill of Countings
BOR.....	Bureau of Reclamation
CAPCO.....	Central African Power Corporation
CORS.....	Continuous Operating Reference Station
GCPs.....	Geodetic Control Points
GNSS.....	Global Navigation Satellite System
GDM.....	Geodetic Deformation Monitoring
GOCA.....	GNSS/LPS-based Online Control and Alarm System
LPS.....	Local Positioning Sensors
NB.....	North Bank
PAN.....	Prism Array Network
RIS.....	Reservoir Induced Seismicity
RTS.....	Robotic Total Station
SB.....	South Bank
UNZA.....	University of Zambia
ZRA.....	Zambezi River Authority